

TECHNICAL DATA SHEET

ACTASOL GEL

Thickened Solvent for Aeronautical Use

DESCRIPTION

Developed for use in the aerospace industry, Actasol Gel is a thickened solvent blend and low volatility substitute for Methyl Ethyl Ketone (M.E.K.), 1,1,1 Trichloroethane, Toluene and blends of M.E.K. and Toluene. With the ability to cling on surfaces, Actasol Gel is made especially for surface preparation, general solvent cleaning and removal of corrosion preventative coatings (CIC) and unwanted stickers/labels.

FEATURES & BENEFITS

- Solvent gel replacement for some mineral spirits and thinners.
- Clings to surfaces to improve penetration and removal.
- Scents from natural sources
- Cleans oily and soiled surfaces with extra penetration.
- Can clean surfaces prior to painting and sealing
- CIC remover.



APPLICATION

Actasol Gel is suitable for general degreasing and cleaning of all oily and soiled aircraft surfaces including wing leading and trailing edges, hydraulic pipes, landing gear and wheel wells. Actasol Gel can be used as a surface cleaner prior to painting and sealing of aircraft components.

It can remove all CIC (Corrosion Inhibiting Compounds) from all areas of aircraft, below floor structure, side wall structure, doors and wheel well areas.

DIRECTIONS FOR USE

- 1) Actasol Gel is used as supplied.
- 2) Applied by brush, rag, scotch brite pad as appropriate and agitate Actasol Gel on the surface to be cleaned.
- 3) For stickers/labels with adhesives, leave to dwell for 5 to 10 minutes before removing using a fine abrasive pad or scraper. Solvent residues on cleaned fabrics can be removed using absorbent cloths or a mild alkaline cleaning solution.

APPROVALS

- Boeing BSS7432
- AMS 1526C (Partial Testing)

PHYSICAL PROPERTIES

Appearance: Clear thick liquid
Flashpoint (°C) PMCC: 48

TECHNICAL DATA SHEET

Specific Gravity (20°C):	0.84
Solubility:	Not water soluble
Odour:	Citrus and forest mint
Dry Time:	Similar to water
Storage:	Store with container closed at room temperature
Shelf-life:	5 years
Effect on metal:	Nil

ORDERING INFORMATION

Product Code	Packaging	Units/Carton
5252/30	1 Litre	16 units
5252/39	4 Litres	4 units
5252/51	20 litres	Each
5252/64	200 litres	Each

WARNING

Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects.

PRECAUTION

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing mist/vapours/spray. Avoid release to the environment.

FIRST AID: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Collect spillage. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

DISPOSAL & STORAGE

Dispose of contents/containers in accordance with local regulations. Store in a well-ventilated place. Keep cool. Store locked up.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 15 Mar 2023 Modified 1st March 2024 Date Printed 11/03/2024 6:46 PM