

TECHNICAL DATA SHEET

W450 DISINFECTANT SPRAYER

Mobile Disinfectant Sprayer for the Decontamination of Surfaces

DESCRIPTION

W450 DISINFECTANT SPRAYER is an electrical spraying machine conceived to treat surfaces by spraying a thin and homogenous mist with the high efficacy disinfectant cleaner KI-OSE®. It was designed to meet the needs of most demanding professionals. W450 DISINFECTANT SPRAYER allows a quick disinfection of areas.

FEATURES

- Lightweight and compact with long-life, powerful turbine
- **Base unit can be placed on the ground or can be carried using the convenient shoulder strap, for facilitated operations.**
- 'Connect & Disinfect' practical system (cord).
- Interchange gun front end to refill quickly and clean
- Small nozzle gives a perfect fine atomization for spraying disinfection.
- Fully adjustable flow dial for precision spraying.
- Spray jet angle can be adjusted horizontally or vertically.
- New disinfection nozzle sprays an average particle size of 25µm.
- Solution cup : 800mL non-topple capacity cup to disinfect up to 200m² with one filling.



CHARACTERISTICS


- Weight : 2.0 kg
- Flow rate: Fully adjustable, 0 to 180 mL/min
- Atomization power: 110 Watts
- Power: 460 Watts
- Tank capacity : 800 mL

RECOMMENDATIONS

Its recommended to use W450 DISINFECTANT SPRAYER with KI-OSE® range.

To ensure the efficacy of the disinfection, all surfaces must be totally homogeneously covered with KI-OSE® ready to use solution with a rate between 14 and 16 mL/m². The flow rate can be setted with the adjusting screw on the trigger according to working speed.

ORDERING INFORMATION

| Product Code | Product | Electrical Plug Type | Units /Carton | Carton Dimensions (cm) | Carton Weight |
|--------------|---------------------------|--|---------------|------------------------|---------------|
| AR0006620 | W450 DISINFECTANT SPRAYER | Type F  | 1 | 31 x 28 x 19 | 2,3 Kg |

KI-OSE® disinfectant cleaner available in various formats, from 1L to 20L. Ask for Technical Data Sheet.

CERTIFICATIONS AND ACCREDITATIONS

- PSA certified to ISO 9001:2015
- PSA NATO Cage Code: FA2X6

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent. Created 12th May 2021. Modified 1st March 2024. Date Printed 25/03/2024 3:55 PM